


**Wiring Information:**



- A: red (+) Excitation
- B: green (+) Signal
- C: white (-) Excitation
- D: blue (-) Signal
- E: bare GND

**Dimensions in mm**

Rated Capacity	A	B	C	D	E	F	G	H	I	J	Weight (kg)
1,0 kgf m (9,807 Nm)	70	3	55	10	44	40	80	48	66	2x 4- Ø6,5	1,5
2,0 kgf m (19,164 Nm)	70	3	55	10	44	40	80	48	66	2x 4- Ø6,5	1,5
5,0 kgf m (49,035 Nm)	70	3	55	10	44	40	80	48	66	2x 4- Ø6,5	1,5
10 kgf m (98,074 Nm)	70	3	55	10	44	40	80	48	66	2x 4- Ø6,5	1,5
20 kgf m (191,64 Nm)	86	3	80	15	50	40	98	58	78	2x 6- Ø10,5	1,8
50 kgf m (490,35 Nm)	130	5	120	20	80	60	118	58	95	2x 6- Ø10,5	2,7
100 kgf m (980,7 Nm)	136	3	130	20	90	60	146	75	115	2x 6- Ø14	2,9

\*Specifications are subject to change without notice/Copyright Althen 03-2006

abrtl

**ALTHEN GmbH Mess- und Sensortechnik**

Frankfurter Str. 150 - 152  
D-65779 Kelkheim

Tel. : +49(0)6195 70060  
Fax: +49(0)6195 700666

<http://www.althen.de>  
E-Mail: [verkauf@althen.de](mailto:verkauf@althen.de)

