

## mm ERTL


## Features

- Internal electronic circuit
- Measuring range 30 1 000 mm
- Output 4-20rnA, or 0-20rnA or 0-1 OV
- Very stable output signal
- Best solution for automation systems
- Excellent repeatability


## **Technical Specifications**


| Measurement stroke          | 30 to 1000 mm  |
|-----------------------------|--|
| Linearity                   | ±%0,05 (>200mm), ±%0,1 (130-200mm),<br>±%0,2 (75-130mm), ±%0,5 (<75mm) |
| Repeatability               | < 0,01 mm  |
| Resolution                  | Infinite   |
| Output                      | 4-20mA, 0-20mA or 0-10V  |
| Permissible applied voltage | 15-30VDC   |
| Electrical connections      | 4 pin connector  |
| Displacement speed          | < 5 m/s  |


| Mechanical life       | 100 million cycles |  |  |  |  |  |  |  |
|-----------------------|--------------------|--|--|--|--|--|--|--|
| Case dimensions       | 33mmx33 mm         |  |  |  |  |  |  |  |
| Case material         | Anodized aluminium |  |  |  |  |  |  |  |
| Rod diameter          | Ø6 mm              |  |  |  |  |  |  |  |
| Rod material          | Stainless steel    |  |  |  |  |  |  |  |
| Mechanical fixing     | Variable brackets  |  |  |  |  |  |  |  |
| IP degree             | IP 65              |  |  |  |  |  |  |  |
| Operating temperature | -20°C +80°C        |  |  |  |  |  |  |  |
| Storage temperature   | -30°C +90°C        |  |  |  |  |  |  |  |




L=US+189









0-10V Output

| ERTL (mm)                 | 30  | 50  | 75  | 100 | 125 | 130 | 150 | 175 | 200 | 225 | 250 | 275 | 300 | 325 | 350 | 375 | 400 | 450 | 500 | 550 | 600 | 650 | 700 | 750 | 800 | 850  | 900  | 1000 |
|---------------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|
| US<br>(Usefull Stroke)    | 30  | 50  | 75  | 100 | 125 | 130 | 150 | 175 | 200 | 225 | 250 | 275 | 300 | 325 | 350 | 375 | 400 | 450 | 500 | 550 | 600 | 650 | 700 | 750 | 800 | 850  | 900  | 1000 |
| MS<br>(Mechanical Stroke) | 33  | 53  | 78  | 103 | 128 | 133 | 153 | 178 | 203 | 228 | 253 | 278 | 303 | 328 | 353 | 378 | 403 | 453 | 503 | 553 | 603 | 653 | 703 | 753 | 803 | 853  | 903  | 1003 |
| L<br>(Total Length)       | 219 | 239 | 264 | 289 | 314 | 319 | 339 | 364 | 389 | 414 | 439 | 464 | 489 | 514 | 539 | 564 | 589 | 639 | 689 | 739 | 789 | 839 | 889 | 939 | 989 | 1039 | 1089 | 1189 |

|           | Model | Measurement stroke (mm) | Linearity (%)          | Output                                     | Connector / Cable    |
|-----------|-------|-------------------------|------------------------|--|----------------------|
| (example) | ERTL  | 500                     | D                      | V10  | C1                   |
|           | ERTL  | 30 1000 mm              | D : ± %0,05 (standard) | V10 :0-10V<br>I 04 :4-20mA<br>I 20 :0-20mA | C1 : 4 pin connector |

Page 1/1

07.2019 | version 0001

The information provided herein is to the best of our knowledge true and accurate, it is provided for guidance only. All specifications are subject to change without prior notification.

## Althen – Your expert partner in Sensors & Controls | althensensors.com

Althen stands for pioneering measurement and custom sensor solutions. In addition we offer services such as calibration, design & engineering, training and renting of measurement equipment.

Germany/Austria/Switzerland info@althen.de

**Benelux** sales@althen.nl **France** info@althensensors.fr Sweden info@althensensors.se USA/Canada info@althensensors.com Other countries info@althensensors.com



