



°C OTG-M280

Description

The OTG-M280 fiber optic temperature sensor offers the highest performances in the industry. The OTG-M280 sensor uses the well proven technique based on the temperature-dependent bandgap of GaAs crystal as the temperature transduction mechanism. Its small sensing GaAs crystal located at the tip of the optical fiber makes it convenient for tip measurement applications.

Combined with our GaAs (SCBG) signal conditioning technology and with the inherent advantages of fiber optic, the OTG-M280 delivers unprecedented repeatability and reliability in the most adverse conditions such as high level of EM, RF, MR and microwave field environments.

The OTG-M280 is made with industry standard optical fiber and is compatible with all the GaAs (SCBG) signal conditioners. This compact and robust fiber optic temperature sensor is available with different optical cables and sheath options and is customizable according to customer specific applications or for OEM-type applications.

Patent pending

Compatible with any of the GaAs (SCBG) series of signal conditioners




Key features

- $\pm 0,3$ °C accuracy
- Small and robust design
- Outstanding repeatability
- MRI/EMI/RFI and microwave immune
- Intrinsically safe
- OEM-type and custom disposable version

Applications

- Surface and core temperature monitoring in MRI environments
- RF, ultrasound and electro surgery environments
- Temperature monitoring for preclinical and research applications
- MR coil temperature monitoring
- Catheter design

■ Dimensions in mm



■ Specifications

Temperature operating range	20 °C to +45 °C (higher temperature ranges available upon request)
Resolution	0.05 °C
Accuracy	±0.3°C (Total accuracy over the full range from 20 to 45 °C including both signal conditioner and sensor errors) ± 0.8°C and better (Total accuracy including both signal conditioner and sensor errors for higher temperature range)
Response time	220 ms
Operating humidity range	0-100 %
MRI/EMI/RFI susceptibility	Complete immunity
Calibration	NIST traceable
Cable length	1.5 meters standard (other lengths available)
Optical connector	ST standard
Sensor diameter	0.280 mm O.D
Cable sheathing	PVC tight buffer (≤ 85°C) or Teflon™ (≥ 85°C)
Signal conditioner compatibility	All GaAs (SCBG) signal conditioners

All specifications are subject to change without prior notifications

The information provided herein is to the best of our knowledge true and accurate, it is provided for guidance only. All specifications are subject to change without prior notification.

Althen – Your expert partner in Sensors & Controls | althensensors.com

Althen stands for pioneering measurement and custom sensor solutions. In addition we offer services such as calibration, design & engineering, training and renting of measurement equipment.

Germany/Austria/Switzerland
info@althen.de

Benelux
sales@althen.nl

France
info@althensensors.fr

Sweden
info@althensensors.se

USA/Canada
info@althensensors.com

Other countries
info@althensensors.com