



Fiber optic temperature sensor M600

High accuracy gaas-based fiber optic temperature sensor for medical applications

ALTHEN
SENSORS & CONTROLS

°C M600


Description

The OTG-M600 fiber optic temperature sensor offers the highest performances in the industry. The OTG-M600 sensor uses the well proven technique based on the temperature-dependent bandgap of GaAs crystal as the temperature transduction mechanism. Its small sensing GaAs crystal located at the tip of the optical fiber makes it convenient for tip measurement applications.

Combined with the GaAs (SCBG) signal conditioning technology and with the inherent advantages of fiber optic, the OTG-M600 delivers unprecedented repeatability and reliability in the most adverse conditions such as high level of EM, RF, MR and microwave field environments.

The OTG-M600 is made with industry standard optical fiber and is compatible with all the GaAs (SCBG) signal conditioners. This compact and robust fiber optic temperature sensor is available with different optical cables and sheath options and is customizable according to customer specific applications or for OEM-type applications.

Compatible with the GaAs (SCBG) series of signal conditioners




Key features

- $\pm 0,3$ °C total system accuracy
- Small and robust design
- Outstanding repeatability
- MRI/EMI/RFI and microwave immune
- Intrinsically safe
- OEM-type and custom disposable version

Applications

- Surface and core temperature monitoring in MRI environments
- RF, ultrasound and electro surgery environments
- Temperature monitoring for preclinical and research applications
- MR coil temperature monitoring

■ Dimensions in mm



■ Specifications

Temperature operating range	20 °C to +45 °C (higher temperature ranges available upon request)
Resolution	0.05 °C
Accuracy	±0.3°C (Total accuracy over the full range from 20 to 45 °C including both signal conditioner and sensor errors) ±0.8°C and better (Total accuracy including both signal conditioner and sensor errors for higher temperature range)
Response time	220 ms
Operating humidity range	0-100 %
MRI/EMI/RFI susceptibility	Complete immunity
Calibration	NIST traceable
Cable length	1.5 meters standard (other lengths available)
Optical connector	ST standard
Sensor diameter	0.600 mm O.D.
Cable sheathing	PVC tight buffer (≤ 85°C) or Teflon™ (> 85°C)
Signal conditioner compatibility	All GaAs (SCBG) signal conditioners