



mm VLS8000

Description

- Prevent Free-Release Damage
- PT8000 Series (except PT8600)
- Aluminum or Stainless Steel Enclosures
- Ranges: 10, 20, 25, 30, 40, 50, 60 inches

Eliminates internal damage if a cable is broken.

Provide safer operation for mobile applications.

Prevents cable from ever reaching damaging velocity during a free-release.

Ideal for applications requiring frequent connecting and disconnecting.



The patented Velocity Limiting System (VLS) is an option for PT8000 Series cable extension transducers that limits cable retraction to a safe 40 to 55 inches per second.

The VLS option prevents the measuring cable from ever reaching a damaging velocity during an accidental free release. This option is ideal for mobile applications that require frequent cable disconnection and reconnection. It prevents expensive unscheduled downtime due to accidental cable mishandling or attachment failure.


VLS is available for most PT8000 models and options.

Exceptions include:

- PT8600 – all configurations.
- PT8101, PT8150, PT8420 and PT8510:
 - medium and high cable tension
 - 2, 5 and 15-inch stroke ranges.

Use the ordering guide to the right to configure the VLS model number.

Ordering Information



creating VLS model number (example):

1. select PT8000 model
2. remove "PT" from the model number
3. add "VLS"
4. completed model number !

PT8101-0060-111-1110
~~PT~~ **8101-0060-111-1110**
VLS + 8101-0060-111-1110
VLS8101-0060-111-1110

**Note: please contact factory for a solution to options not supported.

The information provided herein is to the best of our knowledge true and accurate, it is provided for guidance only. All specifications are subject to change without prior notification.